

## GLASS MOSAIC TEST PERFORMED INFORMATION

Test results apply to all series.

TEST PERFORMED		CONCLUSION
ASTM C650-04 Chemical Resistance	No Effects	Class A
ANSI A 137.2 - 7.9 Thermal Shock Resistance		No Defects
ASTM C648 Breaking Strength		Passes
ASTM C373 Water Absorption		Impervious
ASTM C424 Crazing Resistance		Passes
ASTM C499 Facial Dimensions/Thickness		Passes
ASTM C485-09 Warpage		Passes
ASTM C1026-13 Freeze Thaw		Passes
DCOF Acutest Dynamic Coefficient of Friction		.33 - .54

### SHADE VARIATION

V1 - Uniform Appearance

Differences among pieces from the same production run are minimal.

V2 - Slight Variation

Clearly distinguishable texture and/or pattern within similar colors.

V3 - Moderate Variation

While the colors presented on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly

### MAINTENANCE

Standard household glass cleaner, or a neutral mild detergent with water applies to tile, not grout.

### DURABILITY

Residential floors and walls. Commercial walls and light traffic commercial floors.

We seek to continually improve and refine its products/offerings, and reserves the right to make changes in materials, specifications, and pricing without prior notice. For specific product information, please contact us at 231.375.8037.

Occasional variations in color, shade, tone and texture are to be expected in all glass products. Samples do not necessarily represent an exact match to existing inventory.

